



QUOTE

Renegade LXN40 Air Tandem (Model: RENEGADELXN40)

Est. Wt. (with selected options): 16,865# +/- 3%

Capacity: 40 tons in 16-foot length - GAWR and tire ratings determine legal loads

Load Base: 16-foot rigid 2-point load centered in deck

Framework: All main longitudinal members fabricated with 100,000# minimum yield steel flanges with 50,000# webs

Length / Width: 50 feet 1 inch - 102 inches wide

Compatibility: Designed to accept 3rd flip axle - none

Gooseneck Design: Narrow hydraulic removable non-ground bearing - swing radius of 102 inches (11 ft 11 in overall gooseneck length) - set up for wet line operation

Loaded Fifth Wheel Height: 50 in nominal loaded fifth wheel height with 5 ride height positions

Power Source: 13 HP (min.) Gasoline powered auxiliary power unit

Electrical Receptacle: J560 7-pin connector

Deck Design: Flat level deck design

Deck Length: 29 feet 0 inches clear deck length

Loaded Deck Height: 18 inches with 6 inches ground clearance

Crossmembers: On 12 inch centers

Flooring: 1 3/8 inch nominal wood (full width)

Recessed Floor Mounted D-Ring Package: None

Front Ramps: None, front of deck sloped top down to assist in loading with traction cleats

Extension Brackets: Mounting brackets only

Front Bogie Ramp: Sloped steel bogie ramp (full width)

Mini Boom Trough & Traction Cleats: None

Deck to Bogie Connection: Fixed

Number of Axles: 2

Axle Capacity: 25,000 lb. nominal capacity per axle NOTE: GAWR determined by suspension type, brakes, tires and other components.

Axle Spread: 54.5 inches (between axles)

Brakes: 16.5 inches x 7 inches with 5.5 inches autoslacks - heavy duty brake drums - outboard mount

Spring Brakes: Spring brakes (2 axles)

Suspension: Air ride with automatic controls

Dust Shields: None

Suspension: Air ride with automatic controls

Tires: 255/70R 22.5 H ply OEM Standard

Wheels: 8.25 x 22.5 LVL One buffed outside/steel inside - hub-piloted

Covered Rear Bogie: Rear bogie platform with 1 1/8 inch wood floor

Rear Bogie Height: 40 inches

Bumper: 3 tail light package

Connections for Future Axle Attachment: Air and electrical connections to go along with connecting ears

Width: 8 feet 6 inches

Electrical System: DOT sealed beam and harness with LED lights

Flip Axle: None

Dust Shields on Flip Axle: None

Flip Axle Strobe Light Kit: None

Paint: Fontaine black polyurethane enamel

Lash Rings: 7 pair - 14 total

Flag Holders: 2 pair flag holders

ABS: 4S/2M system without diagnostic tool and cable

Liquid Filled Gauge: Included

Marker Lights: 7 marker lights per side including mid-turn	
Accent Package: Stainless steel bumper insert	
VIN Plate: Bilingual VIN plate	
Registration/Document Holder: Install registration/document holder	
Please Note: Price includes commodity surcharges	
Commercial Terms: Ex Works- Springville, AL, USA	
Total Weight	Est. Wt.: 16,865# +/- 3%