



**A70HDGC-M (Alpha Series Hydraulic Detachable Double Drop Mini Deck)**

**Capacity** 70,000 lbs.  
**Concentrated** 60,000 lbs. in 16'  
**OAL** 53'     **OAW** 102"

**Gooseneck**

10' 5" Hydraulic Detachable  
 49" 5th Wheel Height  
 15" King Pin  
 80" Swing Clearance  
 2 Bent D-Rings Per Side  
 lightning holes each side of Platform  
 5 Position Ride Height  
 Full Width Platform  
 Stainless Mudflaps

**Sub Frame**

9' Long  
 40" Loaded Deck Height  
 Full Width Decking  
 1 Pair Flag Holders  
 1 pair Stake Pockets in Tail Channel  
 Two Pair of Chain Drops in Center  
 One Pair of Pan D-Rings at Rear  
 Frame Reinforcement for Flip Axle

**Main Deck**

33' 7" Length  
 8" Fabricated I-Beams  
 12" Loaded Deck Height  
 4" Ground Clearance  
 4" Cross Members on 18" Centers  
 8 Bent D-Rings per Side  
 Chain Slots on 36" Centers each side  
 1 1/8" Apitong Flush Decking-Full Width  
 Front Ramps tapered to 4" W/Traction Bars

**Axles and Suspension**

2 - 25,000 lb Axles  
 54" Axle Spacing  
 Ridewell Suspension  
 16 1/2" x 7" Drum Brakes  
 4S2M ABS  
 Spring Brakes on Both Axles  
 Raise & Lower Valve  
 Manual Ride Height Control  
 255/70R22.5 Tires  
 8.25 x 22.5 Steel Wheels

**Lighting**

2 Tail Light Package with Stainless Steel Covers  
 2 Pr. Side Markers/ 1 Pr. Mid-Turns in Deck  
 Grote Ultra Blue-Seal Wire Harness

