



7385

A80HDGC (Alpha Series Hydraulic Detachable Double Drop)

Capacity	80,000 lbs.	
Concentrated	70,000 lbs. in 16'	
OAL	48'	OAW 102"
Gooseneck		
	10' 5" Hydraulic Detachable 49" 5th Wheel Height 15" King Pin 80" Swing Clearance 2 Bent D-Rings Per Side Lighting holes each side platform 5 Position Ride Height Full Width Platform Stainless Mudflaps	
	Sub Frame	
	9' Long 40" Loaded Deck Height Full Width Decking 1 Pair Flag Holders 1 pair Stake Pockets in Tail Channel Two Pair of Chain Drops in Center One Pair of Pan D-Rings at Rear Frame Reinforcement for Flip Axle	
Main Deck		
	28' 7" Length 12" Fabricated I-Beams 18" Loaded Deck Height 6" Ground Clearance 6"/4" JRI Beam Cross Members ALT on 12" Centers 8 Bent D-Rings per Side Chain Slots on 24" Centers each side 1 1/8" Apitong Flush Decking-Full Width Front Ramps tapered to 4" W/Traction Bars Removable Swingout Outriggers on 12" Centers	
	Axles and Suspension	
	2 - 25,000 lb Axles 54" Axle Spacing Ridewell Suspension 16 1/2" x 7" Drum Brakes 4S2M ABS Spring Brakes on Both Axles Raise & Lower Valve Manual Ride Height Control 255/70R22.5 Tires 8.25 x 22.5 Steel Wheels	
Lighting		
	2 Tail Light Package with Stainless Steel Covers 2 Pr. Side Markers/ 1 Pr. Mid-Turns in Deck Grote Ultra Blue-Seal Wire Harness	

