



Trailer Model: *Kalyn SlideMAXX TT-2A-35T-51*

Net Capacity:	55 Tons	70,000 lbs. Distributed 50,000 lbs. Concentrated in 10'
Nominal:	51 feet OAL	
	8 feet 6 inches Wide	

GOOSENECK:

9'-6" Gooseneck Length with cut-outs for flush mount transition lights

48" Loaded 5th Wheel Height, 18" Kingpin Setting

86" Swing Radius

20,000# Planetary Winch With Air Clutch; 100' of 5/8" Cable

LED Work light bar on winch

Trailer Operation: Wet kit (3/4" Hydraulic Quick Couplings)

Integrated Top-Mounted Tool Boxes in Neck

Landing gear: Pin-drop stands

DECK:

Nominal Deck Length: 40 feet

Nominal Deck Width: 102 in

Loaded Deck Height: 38 in

4 Beam design: 100,000 psi yield flanges & 80,000 psi yield web minimum

15" tall main beams and 15" tall side rails

3" I-beam cross members on 9" Centers, 1-3/8" Apitong Deck(full width)

Double Key Hole Chain Slots in Upper Flange on 36" Centers

Double Key Hole Chain Slots Along Center of Deck on 36" Centers

Traction Plate Over Wood Rear Approach w/ tiedowns

6' Upper Deck Ramp (air operated)

SUSPENSION:

25,000 lb nominal capacity with Oil seals, 5/8" wall, tapered spindles

50" axle spacing 71" track

12-1/4" x 7-1/2" Brakes ABS Module: 4S2M

Auto Slack Adjusters and Spring Brakes on all Axles

6.75 x 17.5 Hub Piloted Disc Wheels

235/75 R 17.5 16PR Tires Manual Dump Valve

Suspension: Ridewell or Equivalent Air ride Air Ride

Alignment Bracket for Sliding Suspension

GENERAL:

12 Volt System with 7 way Sealed Harness

DOT Rubber Mounted Sealed Beam LED Lights

Epoxy Primer & Black Polyurethane Paint

Wireless Remote for Winch

Heavy Duty DOT Approved Bumper

Red & White Conspicuity tape KS Mud Flaps

LED marker lights every 3' each side including mid turn

Strobe light with toggle switch on rear

High Visibility Light Pkg - 1 pr. Swing out side turn / flashing lights

Models

☐

☒ 2 Axle, 35 Ton, 51' Model

☐

☐

Options

☐ AirWeigh Load Scales

☒ Tire Inflation System

☒ Central Lube - 18 Point Manual

☐ 30,000 Lbs. Winch

☐ Bolt-on Step & Handle

☐ Underglow

☐ Hubodometer

☐ Add itional D-Rings 0 Pairs

☐ Alternating Stake Pockets & Chain Slots

☒ Rub Rail with Single Pipe Spools

☐ Dust Shields

☐ Aluminum Wheels Inside all Axles

☒ Aluminum Wheels Outside all Axles

☒ OEM 235/75 R 17.5 16PR Tires price is mounted on selected wheels

☐ Michelin 245/17.5 Tires